

# AUTOMATIC TAPING MACHINE **COM**® JD II SERIES

DESK TOP TYPE FOR PAPER TAPE OR FILM TAPE

**Highly efficient, secure banding of a wide variety of works.**

## ■ FEATURES

- Banding can be several times more efficient than that of hand taping.
- You can set the heater temperature by digital temperature control system.
- You can count the number of banded workpieces by counter system.



JD II -150F



JD II -240

## ■ CAPABILITY

Model	Product size	Speed
JD II -150F	Max. (width 150mm, height 140mm) Min. (width 30mm, height 5mm)	25 cycles/minute (approx.)
JD II -240	Max. (width 240mm, height 170mm) Min. (width 30mm, height 5mm)	

## ■ MACHINE SPECIFICATIONS

Model	Tape width (mm)	Width	Height	Depth	Table height	Power supply	Allowable tape
JD II -150F-20/30	20mm/25mm/30mm/40mm	425mm	400mm	287mm	230mm	115V/220V/230V/240V 50Hz/60Hz	Film tapes
JD II -240-20/25/30				300mm			Paper tapes
JD II -150F-40	435mm	300mm	300mm	Film tapes			
JD II -240-40				Paper tapes			

## ■ COM TAPE SPECIFICATIONS

Type	Width	Thickness
Paper	20mm/25mm/30mm/40mm	70g (brown)/80g (white)
Film	20mm/30mm/40mm	80 micron/100 micron/MAGIC CUT 110 micron

●Note: Use only the tapes supplied or approved by the machine manufacturer.

●Other than tapes mentioned above; color tapes, printed tapes, etc., can also be made to order.

●Specifications subject to change without notice.

**COM is Communication.**

**TAIYO SEIKI CO.,LTD.**

Head Office: 4-3-7, Hino, Daitoh, Osaka, 574-0062, Japan.

Phone: 81-72-873-3739 Fax: 81-72-875-4324

U R L : <http://www.com-machine.co.jp>

E-mail: [taiyo@com-machine.co.jp](mailto:taiyo@com-machine.co.jp)